

# TAPECONCURRENT

## Product datasheet 1350

### 1. DESCRIPTION :

A polypropylene carrier in combination with a no noise, super high tack acrylic adhesive.

### 2. APPLICATION :

designed for manual or automatic carton sealing, suitable for recycled cardboard.

### 3. CHARACTERISTICS :

Carrier	: Polypropylene
Thickness [ $\mu\text{m}$ ]	: 35
Total thickness [ $\mu\text{m}$ ]	: 65
Adhesive	: Acrylic No Noise
Colour	: Transparent, Brown or White
Adhesion to steel [N/25mm]	: 8.0
Tensile strength [N/cm]	: 55
Elongation [%]	: 140

### 4. AVAILABLE SIZES :

Width [mm]	: 38, 48. Other dimensions upon request.
Length [m]	: 66, 1000. Other dimensions upon request.

### 5. CONDITIONS :

Store in a cool dry place away from sunlight and direct heat sources.  
As far as the storage conditions are respected, the product is guaranteed 12 months.

### 6. DISCLAIMER :

All statements, technical information and product recommendations are based on tests in our laboratories we believe to be reliable. In all cases the user should however determine the suitability of the product for his intended use and user assumes all risk and liability whatsoever in connection therewith. Neither seller or manufacturer shall be liable for any loss or damage - direct, incidental or consequential - arising from the use of the product. Details of test methods are available on request.